

Model No. : >

# IP Color View Dome CAMERA



**AGS-1045I4PDC**

> Main Features :



HD Video




Smart IR



Weather Proof



H.265+



ONVIF

ONVIF 2.4



P2P

## > Specifications :

Camera Model	AGS-1045I4PDC
Image Sensor	1/3" target surface CMOS Image Sensor
Resolution	4MP
Effective Pixels	2560*1440@25, 2304*1296@25 , 1080P@25
Compression	Support H.265 intelligent coding
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination	Color 0.05Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Lens	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	4MP
Night Vision	
Infrared LED	2 warm Led
Infrared Distance	25M
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, TCP, UDP , DHP, RTP , RTSP, DS , DDNS , NTP
ONVIF	Support ONVIF 2.4 (Profile S/T)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2560*1440 @25fp
Main Stream 2	2304*1296 @25fp
Main Stream 3	1920*1080@25fps
Sub Stream 1	"640*360 D1 (default)
Sub Stream 2	"352*288 ( CIF )
Audio	Inbuilt Mic ( G.711U , G.711 A )
Smart Phone	iPhone, iPad, Android, Android Pad

## > Specifications :

Camera Features	
Day/Night	Color/ Color B&W (IR-CUT )
Image Config	Saturation/ Brightness/ Contrast/ Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Corridor Pattern`	Support
BLC	Support
WDR	DWDR: 50dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Czech, Vietnamese
General	
Housing/ Weatherproof Standard	Plastic / IP65
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C Rh95% Max
Power Source	DC12V±10%, 900mA