

Model No. : >

# IP Color View BULLET CAMERA



## AGS-2046I5PDC

> Main Features :



HD Video




Smart IR



Weather Proof



H.265+



ONVIF

ONVIF 2.4



P2P

## > Specifications :

<b>Camera Model</b>	<b>AGS-2046I5PDC</b>
Image Sensor	1/2.8 " target surface CMOS Image Sensor
Resolution	5MP
Effective Pixels	2880*1620@25, 2560*1440@25, 2304*1296@25, 1920*1080@25,920*1080@30
Compression	Support H.265 intelligent coding
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination	Color 0.05Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
<b>Lens</b>	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5MP
<b>Night Vision</b>	
Infrared LED	4 warm Led
Infrared Distance	25M
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, TCP, UDP , DHP, RTP , RTSP, DS , DDNS , NTP
ONVIF	Support ONVIF 2.4 (Profile S/T)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2880*1620@25
Main Stream 2	2560*1440@25
Main Stream 3	2304*1296@25
Sub Stream 1	"640*360 D1 (default)
Sub Stream 2	"352*288 ( CIF )
Audio	Inbuilt Mic ( G.711U , G.711 A )

## > Specifications :

Camera Features	
Day/Night	Color/ Color B&W (IR-CUT )
Image Config	Saturation/ Brightness/ Contrast/ Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Corridor Pattern`	Support
BLC	Support
WDR	DWDR: 50dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Czech, Vietnamese
General	
Housing	Metal, Ip67
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C Rh95% Max
Power Source	DC12V±10%, 900mA