

4MP WDR Network IR-Bullet Camera 50Mtr.



AGS-208514



Main Features :

- 1/3" 4MP PS CMOS Image Sensor (0.84667 cm)
- Max. 4MP(2560 × 1440)@25/30fps and 4MP(2688 × 1520)@20fps
- Instastream and H.264+ dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR,ROI, AWB, AGC, BLC, HLC
- 2.8mm~12mm Motorized Lens
- IR Range of 50 Mtrs, IP67, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro

> Specification:

Feature	
Image Sensor	1/3" 4MP Progressive scan CMOS (0.84667 cm)
Minimum Illumination	0.03Lux@F1.7
Effective Pixels	2688(H) x 1520(V)
Shutter Speed	Auto/Manual, 1/3~1/100000s
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Lens	2.8mm~12mm Motorized lens
Gain Control (AGC)	Auto/Manual
Video Compression	Instastream/H.265/H.264+/H.264/H.264B; MJPEG
Angle of View	Horizontal: 98°-31° Vertical: 55°-18° Diagonal: 116°-36°
Back Light Compensation	BLC / HLC / WDR(120dB)
Video Streaming	Main Stream: 2688 × 1520 (1 fps-20 fps) 2560 × 1440 (1 fps-25/30 fps) Sub Stream: 704 × 576 (1 fps-20/25 fps) 704 × 480 (1 fps-20/30 fps)
Resolution	2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480)
Motion detection	OFF/ON (4 areas, rectangular)
Privacy Mask	4 areas
ROI	Yes (4 areas)
Bit Rate	H.264: 32 Kbps-6144 Kbps, H.265: 12 Kbps-6144 Kbps
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP; ONVIF (Profile S/Profile G); InstaOn; CGI
Ethernet	RJ-45 (10/100Base-T)
Event Trigger	Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
User Account	20 Users
Smart Phone	iPhone, iPad, Android Phone
IR	IR Range of 50 Mtr.
Micro SD	FTP; Micro SD card (support max. 256 GB); NAS
Operating Temperature	-30°C to +55°C (-22°F to +131°F) /less than≤95%
Power Source	DC12V, PoE (802.3af)
Power Consumption	< 7.5W (PoE)
Weatherproof Standard	IP67
Casing	Metal + Plastic
Dimension	243.5 mm × Ø90.7 mm
Weight	0.44 kg