

> 4MP 4G SMART BULLET CAMERA



AGS-2048I4-4G-WIFI

FEATURES

- 4 MP Resolution
- 128GB SD Card support
- Two way audio communication
- Infrared and white dual-light design
- All time color vision with 3 adjustable night vision modes
- Smart human & area movement detection
- Mobile notification on human/motion detection
- Customized pre-recorded alarm broadcast
- Mobile app and PC client software for remote monitoring
- All 4G Sim Card Supported
- Compatible with all ONVIF supported NVR



4G



SD Card



Human Detection



2 Way Intercom



Voice Prompt



IP66

Technical Specifications

| | |
|----------------------|--|
| Product code | AGS-2048I4-4G |
| Image Sensor | 1/2.7" CMOS Sensor |
| Resolution | 2304x1296 |
| S/N Ratio | > 39.1 dB |
| Minimum Illumination | Color: 0.001 Lux, BW: 0 Lux |
| Lens | 4MM Fixed lens |
| White LED | 4 Array LED |
| Infrared LED | 4 Array LED |
| Light Mode | Full color/Infrared/Intelligent |
| White IR Distance | >15 Meters |
| Infrared IR Distance | >20 Meters |
| Image Settings | Image style selection: standard, bright, and gorgeous (adjust the settings through the TRUECLOUD APP) |
| OSD | Date Time & Title |
| White Balance | Auto |
| Day & Night | Auto / Color / B & W |
| 3D-DNR | Auto |
| Mirror/Flip | On / Off |
| Video Streaming | H.264+/H.265/H.265+ 2048 x 1536 @ 15 fps H.264+/H.265/H.265+ 640 x 480 @ 15 fps |
| Features | Motion detection, alarm information push, support mobile phone, Client remote monitoring |
| Audio Streaming | AAC/G711A |

| | |
|--------------------------------|--|
| Audio IN | Built in MIC |
| Audio OUT | Built in Speaker |
| Button | For matching code, reset |
| TF /SD card | 128GB max |
| Protocol | N1 |
| Connectors | RJ 45 for Lan connection / Power input |
| Connection mode | 4G/ Network cable |
| Light Mode | Blink means configure mode, On means connection mode |
| Power Input | DC Input 12V – 1A |
| Power Consumption | ≤5W |
| Operation Temperature/Humidity | -10°C ~ +50°C / 30% to 80% RH |
| Storage Temperature/Humidity | -20°C ~ +60°C / 20% to 90% RH |
| Dimension | (H)71*(W)72*(D)190 mm |
| Housing type | Metal Body Housing (IP66) |