

Model No. : >

NETWORK VIDEO RECORDER



AGS-NV64

> Main Features :



H.265



HD



DDNS



NETWORK



PTZ



AUDIO




MIC



MOBILE



CMS



USB



E-MAIL



MOUSE



4K HD

- ✓ Support 64 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P/960H/D1/CIF IP input
- ✓ H.265 /H.265+/H.265/H.254 high profile compression
- ✓ Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- ✓ Multi-mode recording: manual / timer / motion / sensor/POS/AI Recording
- ✓ Playback : 16 CH simultaneous playback
- ✓ Search : time slice, time, event (manual, sensor, motion), tag search
- ✓ Express and flexible backup via USB, network and so on
- ✓ Pentaplex : preview, record, playback, backup and remote access
- ✓ DHCP, DDNS, PPPoE network protocol and CMS supported
- ✓ Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- ✓ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-user online simultaneously
- ✓ Authorization management, log view and device status view 4K output, true high resolution display
- ✓ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ✓ Support NAT function and QRCode scanning by mobile phone and PAD
- ✓ Powerful smart phone & Pad surveillance with iOS and Andriod OS

> Specifications :

Model		AGS-NV64
System	Compression	Standard H.265S, H.265+/H.265/H.264
	OS	Embedded Linux
Video	Network Input	64CH IPC input
	Incoming/outgoing Bandwidth	320 Mbps
	Network Input Resolution	12MP/8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P/960H/D1 /CIF
	Output	HDMI × 1 : 3840 × 2160 / 3840 × 2160@fps/1920x1080/1280x1024/1024x768 HDMI 2 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768
Audio	Network Input	64 CH IPC audio input
	2-way Audio	RCA × 1
	Local Output	RCA × 1
Record	Record Stream	Dual stream recording
	Resolution	12MP@20fps;8MP / 5MP / 4MP / 3MP / 1080P / 1280x1024/960P / 720P/960H/D1 @30fps
	Mode	Manual, timer, motion, sensor/POS/AI Recording
Playback	Simultaneous Playback	Max 16 CH
	Search	Time slice / time / event / tag /Smart Search
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Mode	Manual, sensor, motion, exception
	Input	8 CH local alarm input Support IPC alarm input
	Output	4 CH
	Triggering	Record, snap, preset, e-mail, etc.
Network	Interface	Rj45 10 / 100 / 1000 Mbps × 2
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP,HTTPs,802.1x,ONVIF,etc
Mobile Device	OS	iOS, Andriod
Storage	HDD	SATA × 8, up to 8TB per HDD E-SATAx2
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	RS485	YES (full-duplex);connectors for PTZ and keyboard
	USB	USB 2.0 × 2, USB3.0x1
	Remote Controller	YES
Others	Power Supply	ATX 250W
	Consumption	≤ 30W (without HDD)
	Dimensions (mm)	445 × 436 × 90 (W × D × H)
	Work Environment	-10 ~ 50 °C, 10% ~ 90% humidity