

Model No. : >



## AGS-SFB-1100/2200

### > Main Features :

- Single /Multi Lane Flap Barrier with LED
- Housing Material : SS 304
- Indicators : LED for direction with arrow marks
- Bi-directional single passage/ multi passage
- Free passage in the set direction Feature
- Always free or locked Feature

## > Specifications :

<b>Material</b>	
Housing Material	SUS 304 stainless steel outer body
Swing Arms	Acrylic
<b>Electrical</b>	
Operating voltage	Ac220±10% 50 Hz,
Power Supply	12V/24V
Infra Red Sensors	4 Pair
<b>Mechanical</b>	
Standard Size	1200 x 200 x 980 (LxWxH)mm
Channel Width	500~750mm as per standard norms
<b>Operation</b>	
Gate opening time	.8 seconds
Direction	Single or bi-directional
Indicators	LED for direction with arrow marks
Application	Designed for the indoor or outdoor application. It is recommended to use cover for outdoor application
<b>Speed</b>	
Passage Speed	30~35 persons/min
MTCF	3 million operations
<b>General</b>	
Ingress Protection	IP 54
Temperature	Indoor : -25°C to 75°C      Outdoor : -25°C to 75°C
Humidity	5% to 95%
Input interface	Dry contact signal or +12V level signal or DC12V pulse signal with a width of more than 100ms, driving current: > 10mA